

Better Living...



Window planet
Engineered System Windows & Doors
aluminium-upvc

KLASSIQUE®
GLAZINGS & CLADDINGS
FRAMELESS GLASSES

MINIMAL SERIES





TECHNICAL INFORMATION

	PN_12	PN_32	PN_34	PN_44	PN_54	PN_64
INSULATION TYPE	Non Insulated	Non Insulated	Insulated	Insulated	Insulated	Insulated
Facing Width	14 mm	17 mm	17 mm	17 mm	17 mm	17 mm
Installation flush to floor inside	yes	yes	yes	yes	yes	yes
Installation flush to floor both side	no	no	yes	yes	yes	yes
Max leaf height	3 meter	3 meter	4.5 meter	6 meter	8 meter	8 meter
Max leaf width	2 meter	3.5 meter	3.2 meter	3.2 meter	3.2 meter	3.2 meter
Max leaf sq.mtr	5 sq.mtr	6 sq.mtr	12 sq.mtr	18 sq.mtr	18 sq.mtr	18 sq.mtr
Glass thickness	12 mm	32 mm	34 mm	44 mm	54 mm	64 mm
Locking	multipoint	multipoint	multipoint	multipoint	multipoint	multipoint
e_Lock	no	no	yes	yes	yes	yes
e_drive	no	no	yes	yes	yes	yes
Home automation	no	no	possible	possible	possible	possible
Max leaf weight	250kg	350kg	350kg	500kg	2000kg	2000kg

PORTER POSSIBILITY

	PN_12	PN_32	PN_34	PN_44	PN_54	PN_64
Air	300pa	300pa	390pa	Up to 690pa	Up to 690pa	Up to 690pa
Uw	Up to 5 W/m ² K	Up to 3.2 W/m ² K	Up to 2 W/m ² K	Up to 0.7 W/m ² K	Up to 0.6 W/m ² K	Up to 0.5 W/m ² K
Resistance to rain	EN_12208	EN_12208	EN_12208	EN_12208	EN_12208	EN_12208
Resistance to wind	EN_12210	EN_12210	EN_12210	EN_12210	EN_12210	EN_12210
Resistance to burglary	RC-3	RC-3	RC-4	RC-5	RC-5	RC-5
Sound insulation	20 db	24 db	40 db	42 db	44 db	49 db



Team Classic

Classic Tower, 267, New Atish Market, Opp. Sunny Mart,
Gopalpura Bypass, Jaipur - 302020



www.teamclassic.in | www.windowplanet.in



admin@teamclassic.in | sales@teamclassic.in



मेवीने मेवीने
विशुद्ध अमृत पीने योग्य

Specialty hardware & door fitting
DHRUV
Innovative Ideas



ASSOCIATES WITH



CANDOR VIEW
see more